



Spectrum Cutting Solutions Pvt Ltd

Product Data Sheet

“SP-WSS 50”

Product Description:

“SP-WSS 50” is a Semi Synthetic Package, which base on surfactant, Sulphonate Amide, Ester base Chemistry.

“SP-WSS 50” long service life semi-synthetic metalworking fluids, utilizing the finest quality additives to achieve stability in the concentrate, finished blends and the final emulsion.

Typical Properties:

- | | |
|-----------------------------|------------------------|
| 1) Color | : Amber to Dark Brown. |
| 2) Appearance | : Viscous Liquid. |
| 3) PH 5% in Distilled water | : Min 9.5 |

Key performance:

1. Excellent corrosion protection
2. Self-Emulsification
3. Biodegradable
4. Excellent Hard water stability
5. Cost Effective



Spectrum Cutting Solutions Pvt Ltd

Guideline Formulations:

Raw material	Formulation
SP-WSS50	55
DM WATER	44.8
Defoamer	0.1
Total	100.00

Result:

Properties	Formulation
Emulsion stability in 400 ppm	Passes
Cast iron Test as per ASTM 4627 3%	Passes s
Frothing test in ration 20:1& 5:1 in 200 ppm Hard water(IS 1115 P:99)	Passes
Thermal stability at 50 °C(IS 1115 P:100)	Passes
Stability test at 4 °C	Passes



Spectrum Cutting Solutions Pvt Ltd

Dosing :

55-60%

Storage condition:

Store inside warehouse, Temperature condition 10°C to 35°C

Avoid water collecting on barrel top,

Shelf life :

6 month From Date of manufacturing.

Pack size :

50 kgs HDPE Carboy, 200kgs HDPE Drums

For Health & safety please refer MSDS

Guidance information is given as per our knowledge.

Date of preparation: 1.04.2021

Rev No: 00

**Flamingo, Empire, 'A' Wing, Flat No 502, Survey No. 22, Behind Maratha Mandir
Near Pristine Fontana Bldg., Bavdhan (Khurd), Pune -411021, Maharashtra
info@spectrumcspl.com www.spectrumcspl.com**